

I - Amoladoras eléctricas



Your global solution manufacturer

■ Sawing



[Incisor FS] - ICS FS..... I-3



[E-Cut Silent] - E-Cut Silent..... I-4



[Multi Materials Granite] - MMG 17..... I-5



[Multi Materials Granite] - MMG 13..... I-5



[Meteor Blue] - MEB 17..... I-6



[Meteor Blue] - MEB 13..... I-6



[Universal High Performance] - BEL 17..... I-7



[Universal Fast Cut] - STL..... I-7



[Tri-Cut] - SP9..... I-8



[Universal Entry Cast.] - MEZ..... I-9



[Universal Entry] - PLT..... I-9



[Turbo Green] - RHB..... I-10



[Universal Entry] - STS..... I-11

■ Grooving - Mortar Raking




[Easy Cut Gold] - EJF..... I-12

[Incisor FS]




- Intensive work : granite, concrete, all intensive work, all building materials, flint, reinforced concrete, steel, wiremesh reinforcing
- Especially for compact materials or highly reinforced concrete
- Neat and fast cut
- High output, high performance





Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
115	22,2	8	42	13	2,4	SN	ICS1301
125	22,2	9	41	13	2,4	SN	ICS1302
150	22,2	11	41	13	2,4	SN	ICS1303
180	22,2	13	41	13	2,4	SN	ICS1304
230	22,2	15	43	13	2,6	SN	ICS1305

ICS FS



E-Cut Sil.




[E-Cut Silent]



NEW

- Silent blade for sensitive environment
- One specification for each application :
 - (a) Reinforced concrete, all building materials
 - (b) Universal, excellent price / performance ratio
 - (c) Mixed concrete / granite
 - (d) Universal high performance, very fast cut
- EFT segment - Fast and neat cut, without vibration




Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Note	Code
230	22,2	15	43	13	2,6	SN	(a)	MEBS305
230	22,2	15	40	11	2,8	SN	(b)	MERS010
230	22,2	15	43	13	2,6	SN	(c)	MMGS304
230	22,2	15	43	13	2,6	SN	(d)	STLS304

- (a) UX-220 / FS-B13
 (b) UX-218 / FS-BT11
 (c) GX-520 / FS-G13
 (d) UX-560 / FR-SP13

[Multi Materials Granite]





- All construction materials, intensive granite
- Universal multi-purpose
- EFT segments - Neat and fast cut, without vibration
- High output, high performance



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
230	22,2	15	44	17	2,8	SN	MMG1701C

GX-530 / FS-G17

MMG 17



[Multi Materials Granite]





- All construction materials, intensive granite
- Universal multi-purpose
- EFT segments - Neat and fast cut, without vibration
- High output, high performance



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
115	22,2	8	43	13	2,4	SN	MMG1301C
125	22,2	9	40	13	2,4	SN	MMG1302C
150	22,2	11	41	13	2,4	SN	MMG1305C
180	22,2	13	41	13	2,4	SN	MMG1303C
230	22,2	16	44	13	2,6	SN	MMG1304C

GX-520 / FS-G13

MMG 13




MEB 17



[Meteor Blue]



- Reinforced concrete, flint concrete, lintels , semi-abrasive materials, washed concrete
- EFT segments - Neat and fast cut, without vibration



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
230	22,2	15	44	17	2,8	SN	MEB1701C

UX-270 / FS-B17

MEB 13



[Meteor Blue]



- Universal : reinforced concrete, flint concrete, lintels , semi-abrasive materials, washed concrete
- EFT segments - Neat and fast cut, without vibration



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
115	22,2	8	43	13	2,4	SN	MEB1301C
125	22,2	9	40	13	2,4	SN	MEB1302C
150	22,2	11	41	13	2,4	SN	MEB1303C
180	22,2	13	41	13	2,4	SN	MEB1304C
230	22,2	15	44	13	2,6	SN	MEB1305C


UX-220 / FS-B13

[Universal High Performance]



NEW

- Intensive work : granite, concrete, reinforced concrete, all building materials, flint, steel, wiremesh reinforcing
- EFT segments - Neat and fast cut, without vibration
- High output, high performance



BEL 17



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
230	22,2	15	44	17	2,8	SN	BEL1701


UX-530 / FS-UX17

[Universal Fast Cut]



NEW

- Intensive work : granite, concrete, reinforced concrete, all building materials, flint, steel, wiremesh reinforcing
- EFT segments - Neat and fast cut, without vibration
- High output, high performance




STL



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
115	22,2	8	42	13	2,4	SN	STL1311
125	22,2	9	40	13	2,4	SN	STL1301
150	22,2	11	40	13	2,4	SN	STL1302
180	22,2	13	41	13	2,4	SN	STL1303
230	22,2	15	43	13	2,6	SN	STL1304

UX-560 / FR-SP13




SP9

[Tri-Cut]

**NEW**

- Mixed : granite, concrete, asphalt
- High output, high performance
- EFT segments
- Core protection segments



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	No. Prot.	Stock	Code
230	22,2	15	43	13	2,6	3	SN	SP90001

FX-560 / BT-SP9

[Universal Entry Cast.]



NEW

- Universal : granite, concrete, all building materials
- Fast cut, castellated segments
- High output, high performance



MEZ



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
230	22,2	15	40	11	2,6	SN	MEZ0001


UX-219 / FR-BT11

[Universal Entry]



NEW

- Universal : granite, concrete, all building materials
- Fast cut
- Excellent ration price / performance



PLT




Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
115	22,2	7	35	11	2,4	SN	PLT1001
125	22,2	8	35	11	2,4	SN	PLT1002
150	22,2	11	35	11	2,4	SN	PLT1003
180	22,2	12	35	11	2,4	SN	PLT1004
230	22,2	15	40	11	2,6	SN	PLT1005

UX-218 / FS-BT11




RHB



[Turbo Green]



- Washed concrete, reinforced concrete, granite, except very abrasive materials
- Precise and quick cut
- Turbo sintered, continuous rim




Ø	Bore	No. Segm.	Segm. Height	Segm. Width	Stock	Code
115	22,2	1	8	2,4	SN	RHB0001
125	22,2	1	8	2,4	SN	RHB0003
150	22,2	1	8	2,4	SN	RHB0005
180	22,2	1	8	2,4	SN	RHB0006
230	22,2	1	8	2,6	SN	RHB0008

TT-522 / TR85

[Universal Entry]


- Non intensive work : concrete, masonry
- Segments sintered on steel core



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	Stock	Code
115	22,2	8	38	10	1,6	SN	STS1004
125	22,2	9	38	10	1,8	SN	STS1001
180	22,2	14	38	10	2,4	SN	STS1003
230	22,2	18	38	10	2,6	SN	STS1002

UC-110 / STS10

STS



EJF



[Easy Cut Gold]



- Masonry processing, mortar raking, bricks, abrasive to semi-abrasive mortar joints
- Alternated brazing
- Fast cut
- Vertical diamond segments for core protection
- Width of cut : 7,5 mm



Ø	Bore	No. Segm.	Segm. Length	Segm. Height	Segm. Width	No. Prot.	Stock	Code
115	22,2	12	20	7,5	3,6	3	SN	EJF0004
125	22,2	12	20	7,5	3,6	3	SG	EJF0005